

SOFAR 7K~10.5KTLM-G3

7/7.7/8/9/10/10.5 KW

SINGLE-PHASE THREE MPPTs



Product advantages

- Max. efficiency up to 98.1%
- Low start-up voltage, wide MPPT voltage range
- Three MPPTs with 150% DC overload
- Compatible with 500 W+ modules
- I-V curve scanning function
- Natural cooling, no fans, low noise
- Prolonged AC overload compatibility (110%)



Model	SOFAR 7KTLM-G3	SOFAR 7.7KTLM-G3	SOFAR 8KTLM-G3	SOFAR 8.8KTLM-G3	SOFAR 9KTLM-G3	SOFAR 10KTLM-G3	SOFAR 10.5KTLM-G3
Input (DC)							
Max. input voltage	600V						
Rated input voltage	300V						
Start-up voltage	90V						
MPPT operating voltage range	80V-550V						
Number of MPPT trackers	3						
Number of DC inputs	3						
Max. input MPPT current	20A/16A/16A						
Max. input short-circuit current	30A/25A/25A						
Output (AC)							
Rated output power	7000W	7700W	8000W	8600W	9000W	10000W	10500W
Max. apparent power	7700VA	7700VA	8800VA	9900VA	9900VA	10000VA	10500VA
Max. output current	35A	35A	40A	45A	45A	46A	46A
Rated output voltage	UNPE230VAc						
Output voltage range	180Vac-276Vac						
Rated output frequency	50/60Hz						
Output frequency range	45Hz-55Hz/50Hz-65Hz						
Active power adjustable range	0-100%						
THDi	<3%						
Power factor	1 (adjustable 4-0.8)						
Efficiency							
Max. efficiency	98.1%						
European efficiency	97.3%						
Protection							
DC reverse polarity protection	Yes						
Anti-islanding protection	Yes						
Leakage current protection	Yes						
Ground fault monitoring	Yes						
PI-array string fault monitoring	Yes						
DC switch	Yes						
SPD	PIV type II, AC type III						
General Data							
Ambient temperature range	-50°C-60°C						
Self-consumption at night	<1W						
Topology	Transformerless						
Degree of protection	IP65						
Allowable relative humidity range	0-100%						
Max. operating altitude	4000m						
Cooling	Natural						
Dimension(W*H*D)	468*380*187 mm						
Weight	17.5kg						
Display	LCD & Bluetooth APP						
Communication	RS485/WIFI						
Standard	IEC/EN 61000-6-1/3, IEC/EN 61173, IEC 62116, IEC 61727, IEC 61833, IEC 60088-1/2/14/26, IEC/EN 62105-1/2, GB, VDE V 075-1-1, EN 50549-1, ANE 208						

*All specifications are subject to change without notice.